


**■ Features :**

- Built-in switching power technology for worldwide 90 to 264V AC use
- No load power consumption < 0.4W
- Maximum output power: 6W
- Class II power (without earth pin)
- Protections: Short circuit / Over load / Over voltage
- Approvals: CE / CB
- 2 year warranty


**SPECIFICATION**

ORDER NO.	HR05NE03	HR05NE04	HR05NE05	HR05NE06	HR05NE07	HR05NE08	HR05NSABC-XYZ	
OUTPUT	DC VOLTAGE Note.2	4.2V	5V	9V	12V	15V	24V	3~24V
	RATED CURRENT	1000mA	1000mA	660mA	500mA	400mA	250mA	/
	CURRENT RANGE	0~ 1000mA	0 ~ 1000mA	0 ~ 660mA	0 ~ 500mA	0 ~ 400mA	0 ~ 250mA	0~1000mA
	RATED POWER	4.2W	5W	6W	6W	6W	6W	6W
	RIPPLE & NOISE (max.) Note.3	120mVp-p	120mVp-p	120mVp-p	200mVp-p	200mVp-p	200mVp-p	200mVp-p
	VOLTAGE ADJ. RANGE	3V~4.2V	4.2V~5V	5V~9V	9V~12V	12~15V	15~24V	3~24V
		Fixed						
	VOLTAGE TOLERANCE Note.4	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%
	LINE REGULATION Note.5	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	LOAD REGULATION Note.6	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%
	LED INDICATOR	-----						
SETUP, RISE, HOLD UP TIME	3000ms, 50ms, 16ms at full load							
INPUT	VOLTAGE RANGE	90 ~ 264VAC		135 ~ 370VDC				
	FREQUENCY RANGE	47 ~ 63Hz						
	EFFICIENCY (Typ.) Note.7	65%	65%	72%	74%	76%	77%	65%
	AC CURRENT	0.3A/100VAC						
	INRUSH CURRENT (Typ.)	50A/230VAC						
	LEAKAGE CURRENT (max.)	0.25mA / 240VAC						
PROTECTION	OVER LOAD	90 ~ 110% Constant current mode Protection type : Hiccup mode, recovers automatically after fault condition is removed						
	OVER VOLTAGE	135 ~ 180% rated output voltage Protection type : Clamp by PWM IC						
ENVIRONMENT	WORKING TEMP.	0 ~ + 40°C (Refer to output load derating curve)						
	WORKING HUMIDITY	20% ~ 90% RH non-condensing						
	STORAGE TEMP., HUMIDITY	-20 ~ +85°C , 10 ~ 95% RH						
	TEMP. COEFFICIENT	±0.03% /°C (0 ~ 50°C)						
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes						
SAFETY & EMC (Note.8)	SAFETY STANDARDS	UL60950-1, CSA 22.2, EN60950-1 Approved						
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC						
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH						
	EMICONDUCTION& RIATION	Compliance to EN55022 class B, FCC PART 15 class B						
	HARMONIC CURRENT	Compliance to EN61000-3-2,3						
EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,11, Light industry level, criteria A							

OTHERS	DIMENSION	74*29*41.4mm (L*W*H)
	PACKING (Typ.)	81.6g
CONNECTOR	PLUG	Standard type : 1.1Φ* 3.5Φ* 10.5mm, tuning fork type center positive for stock ; Other type available by customer requested
	CABLE	Standard type 24Awg UL2468 output only for stock ; Other type available by customer requested
NOTE	<p>1.All parameters are specified at 230VAC input, rated load, 25℃ 70% RH ambient.                  2.DC voltage: The output voltage set at point measure by plug terminal &amp; 50% load.                  3.Ripple &amp; noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf &amp; 47uf capacitor.                  4.Tolerance: includes set up tolerance, line regulation, load regulation.                  5.Line regulation is measured from low line to high line at rated load.                  6.Load regulation is measured from 0% to 100% rated load                  7.Efficiency is measured at 230VAC.                  8.The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.</p>	

■ Mechanical Specification

