

Product Highlights:

- Designed for LED General Lighting Applications
- Externally adjustable maximum output current through RSET
- Universal AC input (108~305Vac)
- Built-in active PFC provide PF>0.90 over entire input range
- Instant Response (< 0.5s Turn on/off time with soft start)
- Built-in Transient Suppression up to 2.5kV
- Class II power supply
- Industry standard T5 metal case cooled by air convection
- Protections: Short Circuit / Over Voltage / Over Current / Over Temperature
- Dimmable output with flexible architecture
 - DC Dimming (0-10V) (2 wire dimming input)
 - Dimming supports majority of available dimming solutions
 - Step Dimming
 - Wide dimming range from 10% to 100%

**Compliance:**

- Safety: UL8750, cUL, CE
- EMI: FCC Part 15 /18 Class b and EN55015 Compliant
- Materials: RoHS Compliant
- Noise Rating: Class A

Orderable Part Numbers

The part numbers below represent the most common variants for this product but do NOT represent all variants available. If you have a specific Current or Voltage requirement for the target application, please confirm with the EHWZ sales team (sales@EHWZ.com) the exact orderable part number to use. At EHWZ, we are able to accommodate most Current and Voltage combination requests. So don't hesitate to ask about a unit that best suits the application.

Constant Current Variants

Part Number	Output Current (mA)	Output Voltage Range (V)	Load Reg.	Max. Effic.	Max. Output Power (W)
XEL-A026A-024-C1X04	1040	16 ~ 24	±5%	84%	25
XEL-A026A-042-CX900	900	18 ~ 28	±5%	84%	26
XEL-A026A-042-CX700	700	25 ~ 36	±5%	85%	26
XEL-A026A-042-CX550	550	30 ~ 42	±5%	86%	23
XEL-A026A-056-CX500	500	33 ~ 52	±5%	87%	26
XEL-A026A-056-CX450	450	33 ~ 56	±5%	87%	26
XEL-A026A-056-CX350	350	33 ~ 56	±5%	87%	20

- For Constant Current Units, the -Z at the end of the part number means the unit has 0-10V Dimming. For Non-Dimmable units replace the -Z with a -N when ordering. variant.
- cUL is only applicable to units with output voltage below 42Vdc.

General Specification

SERIES		XEL-A026A
OUTPUT	DC VOLTAGE RANGE	16 ~ 56Vdc (see orderable parts table for details)
	RATED CURRENT RANGE	0.35A ~ 1.04A (see orderable parts table for details)
	RATED POWER	up to 26W
	LOAD REGULATION ¹	±5%
	TURN ON/OFF TIME	Turn on < 500ms over full input voltage range, Turn off < 200ms under any dimming condition
INPUT	VOLTAGE RANGE	108 ~ 305Vac
	FREQUENCY RANGE	47 ~ 63Hz
	POWER FACTOR (Typ.)	PF > 0.9 at 80% of load when input range is 120 ~ 277 Vac
	EFFICIENCY (Typ.)	≥ 84 % at 80% of load when input range is 120 ~ 277 Vac
	AC CURRENT (Typ.)	0.4A @ 120Vac and 0.2A @ 277Vac
	INRUSH CURRENT (Typ.)	< 50A @ 25°C, 120Vac or < 60A @ 25°C, 277Vac cold start with full load
	LEAKAGE CURRENT	< 250µA @ 120Vac
DIMMING	THD (TOTAL HARMONIC DIST.)	< 20%
	MODES (For Constant Current models)	Step Dimming DC Dimming Control 0-10Vdc Wide dimming range from 10% up to 100% Dimming over entire input voltage range. Unit capable of interfacing with either sourcing or sinking dimmers
PROTECTION	SHORT CIRCUIT	Hiccup mode protection. Recovers automatically after fault condition is removed
	OVER VOLTAGE	< 30% above the maximum output voltage listed for the specific part number
	OVER CURRENT	< 50% above the maximum output current listed for the specific part number
	OVER TEMPERATURE	Unit turns off when Tc > 85°C
ENVIRONMENT	WORKING TEMPERATURE	-40°C ~ + 70°C at Full Load (Tcase rated for 85C)
	WORKING HUMIDITY	5% ~ 95% RH non-condensing
	STORAGE TEMPERATURE	-40°C ~ + 85°C
	STORAGE HUMIDITY	5% ~ 95% RH non-condensing
	VIBRATION	10 ~ 500Hz, 5G 12min./1cycle, period for 30min. each along X, Y, Z axes

SAFETY & EMC	SAFETY STANDARDS	UL8750, CSA C22.2 No. 250.0-08 (except for 42V-54V), EN61347-1, EN61347-2-13 independent, Design refer to UL60950-1, EN60950-1 Compliant, CE
	EMI CONDUCTION & RADIATION	Compliance to EN55015 Class A, FCC 47CFR Part 15 Class
	HARMONIC CURRENT	Compliance to EN61000-3-2 Class C
	EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8,11; EN61547, light industry level, criteria A
	TRANSIENT SUPPRESSION	2kV (100kHz ring wave at 2kV common mode and differential)
OTHERS	LIFETIME	50,000 hours at case temperature ≤ 85C

Note 1: Load Regulation includes line regulation, load regulation and set-up tolerance

Note 2: All specifications not specifically mentioned are measured at 230Vac and 25°C ambient temperature

Adjustable Output Current

This unit has a feature that allows the user to configure the maximum output current as needed. To use this feature a resistor must be placed between the two RSET wires. The table below has a summary of the expected maximum output current as a function of the value of the resistor across RSET and the figure below outlines the expected behavior. If no RSET is present the unit defaults to the maximum output current specified for the unit. The below table indicates what the maximum output current would be, as a percentage of total max power, for several RSET values. As an example and making the assumption that the user has selected a unit with a maximum output current of 3.26A, the table below outlines what the expected output current values would be for the respective resistor values for the 2A unit.


RSET (kΩ)	Output Current (A)	Output Current (%)
OPEN	1.080	100
0.00	0.545	50.5
1.00	0.665	61.6
2.00	0.741	68.6
3.00	0.794	73.5
4.02	0.833	77.1
4.30	0.842	77.9

RSET (KΩ)	Output Current (A)	Output Current (%)
11.00	0.952	88.1
12.00	0.96	88.9
15.00	0.979	90.7
18.70	0.996	92.2
20.00	1.001	92.6
22.00	1.007	93.2
24.00	1.012	93.7



4.70	0.853	79.1
5.10	0.864	80
5.60	0.876	81.1
6.20	0.888	82.3
6.80	0.9	83.3
7.50	0.909	84.4
8.20	0.921	85.3
8.87	0.93	86.1
9.09	0.932	86.3
10.00	0.942	87.2

27.00	1.019	94.3
30.00	1.024	94.8
33.00	1.029	95.2
36.00	1.032	95.6
40.20	1.037	96
51.00	1.045	96.8
62.00	1.051	97.3
75.00	1.056	97.7
300.00	1.073	99.3
1000.00	1.080	100



Please note that when the maximum output current is set by the value of RSET, the dimming will be proportional to the maximum output value set (i.e. if the max output current is set for 2A and the dimmer input is 5V, the expected current output value would be $2A \cdot 0.5 = 1A$).

Mechanical Details

TBD

Drawing not to scale

Terminals	Colors
Input	White (Neutral)
	Black (Line)
Output	Red (Positive)
	Blue (Ground)
Dimming (CC only)	Purple (Dim +)
	Gray (Dim -)

Case	
Material	Metal
Unit Weight	240 gms
Dimensions	**mm (L) x **mm (W) x **mm (H)

**For more detailed information about this product
please contact EHWZ (Sales@EHWZ.com)**

EHWZ Limited

Email: Sales@EHWZ.com

Website: www.EHWZ.com

The information and specifications contained in this summary sheet are believed to be accurate and reliable at the time of publication, however EHWZ Limited assumes no responsibility for damages caused due to potential errors. Also, EHWZ Limited assumes no responsibility for the use of this product in such way that it infringes on patents or other rights of third parties. No license is granted by implication or otherwise under any patent or patent rights of EHWZ Limited. Specifications are subject to change without notice. It is upto the end user to ensure they have the latest revision of the published specifications.